

OPTIONS AND ACCESSORIES

Mobile Base Frame (for Bottom Discharge) standard clearance of 18" includes steel legs and 6" casters with brake kit Clearance measured from bottom of frame. Consult factory for additional heights.

Mobile Base Frame (for Blower Discharge) includes 6" casters with brake kit only. No support legs.

Feed Hopper with cover may be provided in place of standard Feed Table. All units.

Magnets to catch ferrous tramp metal. May be installed on all Feed Tables & Hoppers.

Dust Collector/Bagger attachment (Blower Discharge) includes blower tube and support.

Safety Limit Switch at Feed Hopper.

Discharge Transition Chute (Bottom Discharge unit & not shown.) For customer supplied vacuum system. Customer must advise of hose diameter for suction connection outlet.

Standard screen selection may be added at any time. Sizes are: 1/32, 1/16, 1/8, 3/16, 1/4, 3/8, 1/2 and 3/4 perforation. Other sizes available. Consult factory.

*220V-single phase motor in place of 230/460V-3ph operation available only up to 10HP sized motor.

NOTE: You must check and verify with your local power supplier that your electric service and wiring can adequately and safely handle these motors and voltages.

STANDARD PACKAGE			
REQUIREMENTS	MODEL 10	MODEL 20	MODEL 30
OPERATING RPM	3500 - 3800	3500 - 3800	2500 - 3000
MOTOR SIZE Blower Discharge Bottom Discharge	2-3 HP 2 HP	5 HP 2-3 HP	10-15 HP 7-1/2 HP
FLOOR SPACE Blower Discharge Bottom Discharge	29"x 36" 24"x 36"	29"x 36" 24'x 36"	38"x 40" 27"x 36"
FEED OPENING	6"X 6-1/4"	9"X 6-1/4"	12"X 6-1/4"
HAMMERS REQ'D.	12	18	30
SHIPPING WGT. Blower Discharge Bottom Discharge	(approx.) 360 lb. 330 lb.	(approx.) 450 lb. 400 lb.	(approx.) 725 lb. 475 lb.

Contact us about Custom Hammer Mills, Stainless Steel or Modified units. We also produce cast iron Grist Mills.

INSIDE THE MILL



Hardened free-swinging steel hammers Heavy ribbed cast iron breaker plate Steel screen sized as required

